IN THE CLAIMS:

Please substitute the following claims for the same-numbered claims in the application:

1.   (Currently Amended) A method for organizing a set of nodes into a minimum number of connected clusters in a wireless transmission system, said method comprising steps of:

using of bits in packets used in the initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;[[.]]

setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

defining Master-designates among said nodes through a statistical procedure and defining remaining nodes as a Slave-designate Slave-designates; and

defining clusters including said Master-designates and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said Master-designate Master-designates and at least one Proxy-Slave is selected for each Master-designate.

2.   (Currently Amended) A method for organizing a set of nodes into a minimum number of connected clusters in a wireless transmission system, said method comprising steps of:

using of bits in packets used in the initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;[[.]]

setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

defining Master-designates among said nodes through a statistical procedure and defining remaining nodes as a Slave-designate Slave-designates; and

defining clusters including said Master-designates and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said Master-designate Master-designates and at least one Proxy-Slave is selected for each Master-designate, said method further comprising a step of communicating between said Super-master-designate of one of said cluster clusters and said Proxy-Slave of other of said cluster clusters such that said Super-master-designate collects information of said clusters from each of said Proxy-Slave having an a predetermined ID.

3. (Currently Amended) The method according to the claim 1, wherein said bits in said packet packets are transmitted in initial stages of discovery of nodes and include information to convey states of said nodes.

4. (Currently Amended) A method for organizing a set of nodes into a minimum number of connected clusters in a wireless transmission system, said method comprising steps of:

using of bits in packets used in the initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;[[.]]

setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

defining Master-designates among said nodes through a statistical procedure and defining remaining nodes as ~~a Slave-designate~~ Slave-designates; and

defining clusters including said Master-designates and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said Master-designates and at least one Proxy-Slave is selected for each Master-designate, and

wherein an interval of an inquiry scan is close to a duration of a scan window for said inquiry scan.

5. (Currently Amended) A method for organizing a set of nodes into a minimum number of connected clusters in a wireless transmission system, said method comprising steps of:

using of bits in packets used in the initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;[[.]]

setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

defining Master-designates among said nodes through a statistical procedure and defining remaining nodes as ~~a Slave-designate~~ Slave-designates; and

defining clusters including said Master-designates and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said

Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein said bits in said packet include information selected from the group consisting of numbers of responses received by said node by a predetermined period, numbers of said nodes included in said cluster, whether or not said node ~~transmitted~~ transmitting said inquiry response is included in said cluster, and whether or not said node transmitting said inquiry response is said Master-designate.

6.   (Currently Amended) A method for organizing a set of nodes into a minimum number of connected clusters in a wireless transmission system, said method comprising steps of:

using of bits in packets used in the initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;[[.]]

setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

defining Master-designates among said nodes through a statistical procedure and defining remaining nodes as ~~a Slave-designate~~ Slave-designates; and

defining clusters including said Master-designates and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said Master-designates and at least one Proxy-Slave is selected for each Master-designate, and

09/634,123   6

wherein said statistical procedure includes Bernoulli trials executed by each node.

7. (Original) The method according to the claim 1, wherein said wireless transmission system is a Bluetooth System.

8. (Currently Amended) A system for organizing a set of nodes into a minimum number of connected clusters of bounded size in a wireless transmission system, said system comprising:

means for using of bits in packets used in the initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;

means for setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

means for defining a Master-designate among said nodes through a statistical procedure and defining remaining nodes as a Slave-designate; and

means for defining a cluster including said Master-designate and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said ~~Master-designate~~ Master-designates and at least one Proxy-Slave is selected for each Master-designate.

9. (Currently Amended) A system for organizing a set of nodes into a minimum number of connected clusters of bounded size in a wireless transmission system, said system comprising:

09/634,123   7

means for using of bits in packets used in the initial stages of a device discovery

procedure, to include information relating to a state of said nodes during the initial stages of the

procedure;

means for setting parameters in the procedure for device discovery to achieve a

separation of the nodes into those in a transmit-state and a receive-state;

means for defining a Master-designate among said nodes through a statistical procedure

and defining remaining nodes as a Slave-designate; and

means for defining a cluster including said Master-designate and at least one said Slave-

designate, wherein said Slave-designate continuously scans for an inquiry message transmitted

from said Master-designate and said Slave-designate transmits an inquiry response to said

Master-designate upon receiving said inquiry message to establish a connection between said

Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said Master-designate and at

least one Proxy-Slave is selected for each Master-designate, said system further comprising

means for communicating between said Super-master-designate of one of said ~~cluster~~ clusters

and said Proxy-Slave of other of said ~~cluster~~ clusters such that said Super-master-designate

collects information of said clusters from each of said Proxy-Slave having ~~an~~ a predetermined

ID.

10.   (Original) The system according to the claim 8, wherein said bits in said packets are

transmitted in initial stages of discovery of nodes and include information to convey states of

said nodes.

11.   (Currently Amended) A system for organizing a set of nodes into a minimum number of

connected clusters of bounded size in a wireless transmission system, said system comprising:

means for using of bits in packets used in [[the]] initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;

means for setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

means for defining a Master-designate among said nodes through a statistical procedure and defining remaining nodes as a Slave-designate; and

means for defining a cluster including said Master-designate and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said Master-designates and at least one Proxy-Slave is selected for each Master-designate, and

wherein an interval of an inquiry scan is close to a duration of a scan window for said inquiry scan.

12.   (Currently Amended) A system for organizing a set of nodes into a minimum number of connected clusters of bounded size in a wireless transmission system, said system comprising:

means for using of bits in packets used in the initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;

means for setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

means for defining a Master-designate among said nodes through a statistical procedure and defining remaining nodes as a Slave-designate; and

means for defining a cluster including said Master-designate and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein said bits in said packets include information selected from the group consisting of numbers of responses received by said node by a predetermined period, numbers of said nodes included in said cluster, whether or not said node ~~transmitted~~ transmitting said inquiry response is included in said cluster, and whether or not said node transmitting said inquiry response is said Master-designate.

13.   (Currently Amended) A system for organizing a set of nodes into a minimum number of connected clusters of bounded size in a wireless transmission system, said system comprising:

means for using of bits in packets used in the initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;

means for setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

means for defining a Master-designate among said nodes through a statistical procedure and defining remaining nodes as a Slave-designate; and

09/634,123

10

means for defining a cluster including said Master-designate and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said Master-designates and at least one Proxy-Slave is selected for each Master-designate, and

wherein said statistical procedure includes Bernoulli trials executed by each node.

14.   (Original) The system according to the claim 8, wherein said wireless transmission system is a Bluetooth System.

15.   (Currently Amended) The system according to the claim 14, wherein nodes which are connected as slaves in a piconet carrying carry on a node discovery on behalf or in addition to said Master-designate such that a piconet/scatternet for the Bluetooth system is formed.

16-18. (Canceled)

19.   (Currently Amended) A computer program product having a computer readable medium having a computer program recorded therein for organizing a set of nodes into a minimum number of connected clusters of bounded size in a wireless transmission system, said computer program product including:

computer program code means for using of bits in packets used in an initial stages of a device discovery procedure, to include information relating to a state of said nodes during the

09/634,123 ·

11

initial stages of the procedure;

computer program code means for setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

computer program code means for defining a Master-designate among said nodes through a statistical procedure and defining remaining nodes as a Slave-designate Slave-designates; and

computer program code means for defining a cluster including said Master-designate and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said Master-designate Master-designates and at least one Proxy-Slave is selected for each Master-designate.

20.   (Currently Amended) A computer program product having a computer readable medium having a computer program recorded therein for organizing a set of nodes into a minimum number of connected clusters of bounded size in a wireless transmission system, said computer program product including:

computer program code means for using of bits in packets used in an initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;

computer program code means for setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

computer program code means for defining a Master-designate among said nodes through a statistical procedure and defining remaining nodes as a Slave-designate Slave-designates; and

09/634,123   12

computer program code means for defining a cluster including said Master-designate and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein ~~wherein~~ at least one Super-master-designate is selected from said ~~Master-designate~~ Master-designates and at one Proxy-Slave is selected for each Master-designate, said computer program further comprising means for communicating between said Super-master-designate of one of said ~~cluster~~ clusters and said Proxy-Slave of other of said ~~cluster~~ clusters such that said Super-master-designate collects information of said clusters from each of said Proxy-Slave having ~~an~~ a predetermined ID.

21. (Currently Amended) The computer program product according to the claim 19, wherein said bits in said ~~packet~~ packets are transmitted in initial stages of discovery of nodes and include information to convey states of said nodes.

22. (Currently Amended) A computer program product having a computer readable medium having a computer program recorded therein for organizing a set of nodes into a minimum number of connected clusters of bounded size in a wireless transmission system, said computer program product including:

computer program code means for using of bits in packets used in ~~an~~ initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;

computer program code means for setting parameters in the procedure for device

discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

computer program code means for defining a Master-designate among said nodes through

a statistical procedure and defining remaining nodes as a Slave-designate Slave-designates; and

computer program code means for defining a cluster including said Master-designate and

at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry

message transmitted from said Master-designate and said Slave-designate transmits an inquiry

response to said Master-designate upon receiving said inquiry message to establish a connection

between said Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said Master-designates and

at least one Proxy-Slave is selected for each Master-designate, and

wherein an interval of an inquiry scan is close to a duration of a scan window for said

inquiry scan.

23.   (Currently Amended) A computer program product having a computer readable medium

having a computer program recorded therein for organizing a set of nodes into a minimum

number of connected clusters of bounded size in a wireless transmission system, said computer

program product including:

computer program code means for using of bits in packets used in an initial stages of a

device discovery procedure, to include information relating to a state of said nodes during the

initial stages of the procedure;

computer program code means for setting parameters in the procedure for device

discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

computer program code means for defining a Master-designate among said nodes through

09/634,123   14

a statistical procedure and defining remaining nodes as ~~a Slave-designate~~ Slave-designates; and

computer program code means for defining a cluster including said Master-designate and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein said bits in packets include information selected from the group consisting of numbers of responses received by said node by a predetermined period, numbers of said nodes included in said cluster, whether or not said node ~~transmitted~~ transmitting said inquiry response is included in said cluster, and whether or not said node transmitting said inquiry response is said Master-designate.

24.   (Currently Amended) A computer program product having a computer readable medium having a computer program recorded therein for organizing a set of nodes into a minimum number of connected clusters of bounded size in a wireless transmission system, said computer program product including:

computer program code means for using of bits in packets used in an initial stages of a device discovery procedure, to include information relating to a state of said nodes during the initial stages of the procedure;

computer program code means for setting parameters in the procedure for device discovery to achieve a separation of the nodes into those in a transmit-state and a receive-state;

computer program code means for defining a Master-designate among said nodes through a statistical procedure and defining remaining nodes as ~~a Slave-designate~~ Slave-designates; and

computer program code means for defining a cluster including said Master-designate and at least one said Slave-designate, wherein said Slave-designate continuously scans for an inquiry message transmitted from said Master-designate and said Slave-designate transmits an inquiry response to said Master-designate upon receiving said inquiry message to establish a connection between said Master-designate and said Slave-designate,

wherein at least one Super-master-designate is selected from said Master-designates and at least one Proxy-Slave is selected for each Master-designate, and

wherein said statistical procedure includes Bernoulli trials executed by each node.

25.   (Original) The computer program product according to the claim 19, wherein said wireless transmission system is a Bluetooth System.

This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

❑ **BLACK BORDERS**

❑ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**

❑ **FADED TEXT OR DRAWING**

❑ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**

❑ **SKEWED/SLANTED IMAGES**

❑ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**

❑ **GRAY SCALE DOCUMENTS**

☑ **LINES OR MARKS ON ORIGINAL DOCUMENT**

❑ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**

❑ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.
As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.